

GX3104

4 CHANNEL PXI SOURCE MEASURE UNIT (SMU), $\pm 20V$, 250MA PER CHANNEL

- 4 isolated, common ground SMU channels
- 4-quadrant operation: $\pm 20 V$, $\pm 1 A$
- 7 current ranges, $\pm 2.5 \mu A$ to $\pm 1 A$ full scale
- Up to 1A capability on one channel
- 24-bit ADC's, 18-bit DAC's
- Supplied with a full featured API and UI
- PXI hybrid slot compatible



DESCRIPTION

The GX3104 is a precision 3U PXI module that forces and senses both voltage and current over a range of $\pm 20 V$ and up to $\pm 1 A$ (channel 1) with channels 2- 4 capable of supplying up to 500 mA. Total available output current from the module is 1A. The four channels are electrically isolated from the PXI power supply and share a common, isolated ground.

FEATURES

The GX3104 employs 18-bit DACs for the sourcing of voltage and current. There are 7 current ranges, ranging from $\pm 2.5 \mu A$ FS to $\pm 1 A$ FS. Measurements employ a 24 bit ADC with programmable resolution from 18 to 24 bits. Each output channel includes SMU output connections, Kelvin (sense) connections, and a driven guard connection for low level current measurements.

SOFTWARE

The board is supplied with the GXSMU library, a software package that includes a virtual instrument panel, and a Windows 32/64-bit DLL driver library and documentation. The virtual panel can be used to interactively program and control the instrument from a window that displays the instrument's current settings and status. In addition, interface files are provided to support access to programming tools and languages such as [ATEasy®](#), LabVIEW, LabVIEW/Real-Time, C/C++, Microsoft Visual Basic®, Delphi, and Pascal. An On-Line help file and PDF User's Guide provides documentation that includes instructions for installing, using and programming the board.

A separate software package - GtLinux - provides support for Linux 32/64 operating systems.

APPLICATIONS

- Semiconductor component test and characterization
- ATE systems
- Board and system level test

GX3104

SPECIFICATIONS

HARDWARE	
I/O Connections per Channel	SMU input / output (2) Guard Kelvin (2)
Connector	DB 25
Format	PXI, 3U single slot, hybrid slot compatible
SOURCE AND MEASURE SPECIFICATIONS	
Voltage Source	Range: ± 20 V FS Accuracy: 0.05% of programmed value + 2mV
Voltage Source Resolution	18 bits
Output Voltage Ripple and Noise	<20 mV p-p, 20 MHz BW, full load
Current Source Resolution	18 bits
Current Source Ranges	± 25 μ A to ± 250 mA, in decade ranges Accuracy: $\pm 0.05\%$ of programmed value + 0.05% of FS range ± 2.5 μ A range Accuracy: $\pm 0.05\%$ of programmed value + 0.4% of FS range ± 1 A range* Accuracy: $\pm 0.5\%$ of programmed value + 0.5% of FS range *Notes: -Only Channel 1 supports the 1A capability- -Channels 2-4 support up to 500 mA FS- -Maximum output current from the module cannot exceed 1A-
Isolation Voltage	± 60 VDC relative to PXI ground
Maximum Voltage Between the LO Terminal and PXI Ground	± 60 V
Absolute Maximum Voltage within a Channel	± 25 Volts
Source Noise	20 μ V (0.1 Hz to 10 Hz) 25 mV RMS (20 Hz to 20 MHz)
Settling Time	10% of current range: 10 μ s typical 90% of current range: 100 μ s typical
Transient Response	Settles to ± 20 mV of programmed value after 80% load change, 100 μ s typical

Voltage Measurement	Range: ± 20 V Accuracy: 0.05% of measured value + 2mV
Current Measurement Ranges	± 25 μ A to ± 250 mA, in decades Accuracy: $\pm 0.05\%$ of measured value + 0.05% of FS range ± 2.5 μ A range Accuracy: $\pm 0.05\%$ of measured value + 0.4% of FS range ± 1 A range* Accuracy: $\pm 0.5\%$ of measured value + 0.5% of FS range *Notes: -Only Channel 1 can measure ± 1 A FS- -Channels 2 -4 can measure ± 500 mA FS
Measurement Resolution	Programmable, 18 to 24 bits
Measurement Conversion Rate	82 μ s to 2868 μ s, based on measurement resolution
ENVIRONMENTAL AND PHYSICAL SPECIFICATIONS	
Temperature Range	Operating: 0 to +40 °C Storage: -20°C to +70 °C
Power	+12 VDC, 100 mA +5 VDC, 7.8 A +3.3 VDC, 4.1 A
Connector	DB 25 female

Note: Specifications are subject to change without notice

GX3104

ORDERING INFORMATION

GX3104	4 Channel SMU, $\pm 20V$, 250mA per Channel
GX3104-M	4 Channel SMU, $\pm 20V$, 250mA per Channel (Ruggedized & Conformally Coated)
CALIBRATION	
GX3104-CAL	GX3104 Calibration/Verification Service. Includes pre-verification data (post calibration data provided if applicable)
GX3104-CAL-3	GX3104 Calibration/Verification Service - 3 Years. Includes pre-verification data (post calibration data provided if applicable)
GX3104-CAL-5	GX3104 Calibration/Verification Service - 5 Years. Includes pre-verification data (post calibration data provided if applicable)
CalEasy-GX3104	CalEasy for the GX3104 (Single User License) with One Year Support and Subscription
CalEasy	CalEasy License for all Supported Marvin Test Solutions Products (Single User License) with One Year Support and Subscription
CalEasy-2Y	CalEasy License for all Supported Marvin Test Solutions Products (Single User License) with Two Year Support and Subscription
CalEasy-3Y	CalEasy License for all Supported Marvin Test Solutions Products (Single User License) with Three Year Support and Subscription
GX3104-CALCABLE	GX3104 Calibration Cable Assembly

GX3104

THIS PAGE INTENTIONALLY LEFT BLANK

ASUREMENT

需要详细资料? 请现在通过 sales@hkaco.com 联系我们

北京 010-5781 5040; 187 1014 9603 | 上海 021-6728 2707; 136 7167 1424
西安 029-8187 3816; 152 9185 3139 | 广州 400-999-3848; 159 8639 3954
成都 028-6138 2617; 136 8841 6951 | 沈阳 024-8376 9335; 157 1053 7541
深圳 0755-22677441 | 武汉 027-8193 9100 | 香港 6749 9159



关注测试专家



hkaco.com

25
YEARS
OF
MAKING TEST EASY

25年多来我们
使测试变容易

广州虹科电子科技有限公司
测试测量与控制产品和解决方案
广州科学城科汇金谷三街2-701

HongKe

虹科